

Remote Audio - Zaxcom Product Compatibility

	Item ID	Description	TRX	STA	IFB	TCA	RX900	ERX	QRX	RX4900	ZFR	Mix 8	Mix 12	Nomad	Deva IV, V, 5.8, Fusion 10	Deva 16, Fusion 12
	BDSCSQN	BDS (5.5 x 2.5 x 12mm) to 4 pin Hirose male. 24 inches.					X		X					X		
	BDSCZENG	BDS (5.5 x 2.5 x 12mm) to 761K (5.5 x 2.5 x 12mm). 24 inches.					X		X			X				
	BDSCZSTA100	BDS (5.5 x 2.5 x 12mm) to 760K (5.5 x 2.5 x 9.5mm). 24 inches.		X	X											
NEW!	CA-2X3FT5F-18	(2) XLR3F to TA5F. Balanced stereo breakout. 18 inches.												X		
	CA-T5F2X3M-18	TA5F to (2) XLR3M. Balanced stereo breakout. 18 inches.							X					X		
	CA-T5FX3M-18	TA5F to XLR3M. Balanced channel one (left) out. 18 inches.							X					X		
NEW!	CA1/8FT5F	3.5mm female to TA5F. Zaxcom Nomad return adapter. 4 inches.												X		
NEW!	CABETAMIXNOMAD	(2) XLR3F and TA5F to Neutricon Male. ENG breakaway mixer end for use with Zaxcom Nomad. 17 feet.												X		
	CABNC1/4	BNC to 1/4 inch tip-sleeve plug. Nomad to timecode slate. 12 inches.												X		
NEW!	CABNCRA	BNC-RA to BNC-RA timecode cable. 15 inches.												X		
	CADEV16F12IN	(4) XLR3F to 10 pin Hirose male. Zaxcom channel 9-12 analog input. 2 feet with 8 inch fan.														X

Remote Audio - Zaxcom Product Compatibility

	Item ID	Description	TRX	STA	IFB	TCA	RX900	ERX	QRX	RX4900	ZFR	Mix 8	Mix 12	Nomad	Deva IV, V, 5.8, Fusion 10	Deva 16, Fusion 12
NEW!	CADEVO16F12	DB25M to (8) XLR3M. Deva 16 and Fusion 12 channel 1-8 analog out. 3 feet with 12 inch fan.														X
NEW!	CADEVO16F12UP	DB25M 45 degree to (8) XLR3M. Deva 16 and Fusion 12 channel 1-8 analog out. 3 feet with 12 inch fan.														X
	CADEVO4/5	DB25M to (6) XLR3M. Deva channel 1-6 analog out. 3 feet with 12 inch fan.													X	
NEW!	CADEVO4/5UP	DB25M 45 degree to (6) XLR3M. Deva channel 1-6 analog out. 3 feet with 12 inch fan.													X	
	CALECSR5	TA5F RA to (2) XLR3M. Balanced stereo breakout. 18 inches.							X					X		
NEW!	CAPTAP761	Anton Bauer P-Tap to 761K (5.5 x 2.5 x 12mm) RA. 14 inches.					X		X							
	CAPWRHIRWSD	XLR4M to 4 pin Hirose male. 4 feet.												X		
	CAPWRX41M	XLR4M to XLR4F. Uses 18AWG Powerflex cable. 4 feet.											X		X	X
	CAPWRX41MHD	XLR4M to XLR4F. Uses 14AWG Powerflex cable. 4 feet.											X		X	X
	CAPWRX4HIR	XLR4M to 4 pin Hirose male. 2 feet.														
NEW!	CAPWRX4M761	XLR4M to 761K (5.5 x 2.5 x 12mm). 4 feet.					X		X	X		X				

Remote Audio - Zaxcom Product Compatibility

	Item ID	Description	TRX	STA	IFB	TCA	RX900	ERX	QRX	RX4900	ZFR	Mix 8	Mix 12	Nomad	Deva IV, V, 5.8, Fusion 10	Deva 16, Fusion 12
NEW!	CAT5FL	TA5F to TA5F. Wired point-to-point. 18 inches.							X					X		
NEW!	CATC1/8BNC	3.5mm RA (ring floated) to BNC RA. 18 inches.		TC In	TC In			TC Out	TC Out					X		
	CATCIO	5 pin Lemo to XLR3M and XLR3F. Timecode in and out. 3 feet with 6 inch pigtail.													X	X
	CATCIOBNC	5 pin Lemo to (2) BNC. Timecode in and out. 3 feet with 6 inch pigtail.												X		
NEW!	CATCLEMO1/8	5 pin Lemo (TC Out) to 3.5mm RA (ring floated). 18 inches.		TC In	TC In											
	CATCLL	5 pin Lemo to 5 pin Lemo. Timecode in and out. 3 feet.													X	X
	CAX3F1/8MS	XLR3F to 3.5mm RA (wired tip-sleeve). 18 inches.		No	No				TBD							
	CAX3M1/8MS	3.5mm RA (wired tip-sleeve) to XLR3M. 18 inches.		TBD	No	TBD								Mono Out, Tape Out		
	CAXSTE	XLR5F to (2) XLR3M. Balanced stereo breakout. 18 inches.					X									
	CAZPCAM	4 Pin Hirose male to 761K (5.5 x 2.5 x 12mm) RA. 10 inches.					X		X					X		
	CAZPCAMY	4 Pin Hirose male to 761K (5.5 x 2.5 x 12mm) and 760K (5.5 x 2.5 x 9.5mm). For powering RX900 and IFB100. 18 inches.			X		X									

Remote Audio - Zaxcom Product Compatibility

	Item ID	Description	TRX	STA	IFB	TCA	RX900	ERX	QRX	RX4900	ZFR	Mix 8	Mix 12	Nomad	Deva IV, V, 5.8, Fusion 10	Deva 16, Fusion 12
	CAZSTA1003YTA5	(2) TA3F to TA5F. Line level source to Zaxcom STA100/150 or IFB100 transmitters. Contains 27K resistors for use with impedance balanced outputs. 18 inches.		X	X											
NEW!	CAZSTA100T5F	TA5F to TA5F. Zaxcom Nomad to STA100/150 or IFB100 adapter. 18 inches.		X	X									X		
	CAZSTA100XYTA5	(2) XLR3F to TA5F. Line level source to Zaxcom STA100/150 or IFB100 transmitters. 18 inches.		X	X											
	CAZSTA100XYTA5R	(2) XLR3F to TA5F RA. Line level source to Zaxcom STA100/150 or IFB100 transmitters. 18 inches.		X	X											
NEW!	CAZTCINBNC	BNC RA to 3.5mm RA (tip floated). For use with QRX100 timecode input. 18 inches.							TC In					X		
NEW!	CAZTCIOLEMO	5 pin Lemo to 3.5mm RA. For use with QRX100 timecode in and out. 18 inches.							TC I/O							
	CAZTRX900TC	XLR3F to 3-pin Lemo. Line level source to Zaxcom transmitter inputs. Contains 40dB pad. 12 inches.	X								X					
	CAZTRX900TCML	XLR3F to 3-pin Lemo. Mic level source to Zaxcom transmitter input. 12 inches.	X								X					
	CAZXSTE	XLR5F to (2) XLR3M. Balanced stereo breakout. Left channel 14 inches. Right channel 12 inches.					X									
	NPADZAX	NP1 battery cup to 761K (5.5 x 2.5 x 12mm) RA. 24 inches.					X		X							